SULFIDE TEST KIT

Code 4456-01 | Octa-Slide 2, 0.2-20.0 ppm



QUANTITY	CONTENTS	CODE		
30 mL	*Sulfide Reagent A	*4458-G		
15 mL	*Sulfide Reagent B	*4459-E	-	
60 mL	Sulfide Reagent C	4460-H	*Reagent is a potential health	
2	Test Tubes, 2.5-5-10mL, plastic, w/caps	0106	hazard. READ SDS: lamotte.com Emergency information:	
1	Pipet, 1.0 mL, plastic	0354	Chem-Tel USA 1-800-255-3924 Int'l, call collect, 813-248-0585	
1	Sulfide Octa-Slide 2 Bar, 0.2-20.0 ppm	4457-01		
1	Octa-Slide 2 Viewer	1101	SDS O	
To order individual reagents or test kit components, use the				

Warning! This set contains chemicals that may be harmful if misused. Read cautions on individual containers carefully.

Not to be used by children except under adult supervision.

USE OF THE OCTA-SLIDE 2 VIEWER

Note: Collect sample with a minimum of aeration and analyze promptly:

EPA ACCEPTED PROCEDURE

A known concentration of sulfide in the range of 0.2-20.0 ppm S= may be prepared as a check standard by referring to APHA Standard Methods 4500–S2–D, 17th Ed., 1989. Run this test on the check standard. If the test result is incorrect, discard the old reagents and order the reagent refill package.

Continued on next page...

specified code number.

PROCEDURE

Note: Collect sample with a minimum of aeration to analyze promptly:

Tioto. Solicot surripio with a minimum of defactor to driaty25 promptly.					
1. Place Sulfide Octa-Slide 2 Bar [4457-01] into the Octa-Slide 2 Viewer (1101).	2. Fill a test tube (0106) to the 5 mL line with the sample water.	3. Add 15 drops of *Sulfide Reagent A [4458].			
4. Cap and gently invert to mix.	5. Add 3 drops of *Sulfide Reagent B (4459).	6. Cap and mix.			
7. Wait 1 minute.	8. Use the pipet (0354) to add 1.0 mL of Sulfide Reagent C (4460).	9. Cap and mix.			
10. Insert test tube into Octa-Slide 2 Viewer (1101).	11. Hold the Viewer so that non-direct light enters through the back. Match sample color to a color standard. Record as ppm Sulfide.				