SULFATE KIT

Code 7778-01 | Octa-Slide 2, 20-200 ppm



QUANTITY	CONTENTS	CODE
50	*Sulfate Turb Tablets	*6456-H
1	Test Tubes, 2.5-10 mL, plastic, w/cap, with line	0106-WL
1	Octa-Slide 2 Viewer	1101
1	Sulfate Octa-Slide 2 Bar, 20-200 ppm	7779-01

To order individual reagents or test kit components, use the specified code number.

*Reagent is a potential health hazard. READ SDS: lamotte.com **Emergency information:**

Chem-Tel USA 1-800-255-3924 Int'l. call collect, 813-248-0585.







Warning! This set contains chemicals that may be harmful if misused. Read cautions on individual containers carefully. Not to be used by children except under adult supervision.

USE OF THE OCTA-SLIDE 2 VIEWER

PROCEDURE (CHART) 1. 2. Insert Sulfate Fill a test tube Add one *Sulfate (0106-WL) to the Octa-Slide 2 Bar Turb Tablet (7779-01) into 10 ml line with [6456]. the Octa-Slide 2 sample water. Viewer (1101). 4 5. ĥ **Immediately** Hold the Viewer so that Cap and mix until tablet insert test tube non-direct light enters disintegrates. into Octa-Slide 2 through the back. Match Viewer with the sample with standards by printing on the comparing the degree to tube facing away which the black from the operator. lines are obscured by the turbidity (cloudiness) of the sample.

7.

Disregard any differences in color between the sample and the standards. The test is based on the degree of turbidity, not color. Record as ppm Sulfate.

NOTE: Thoroughly clean tubes after each use.